

8

209E	7' 9":
0"	0,90 mm
5"	1,07
10"	1,33
15"	1,55
20"	1,73
25"	1,90
30"	2,06
35"	2,22
40"	2,37
45"	2,53
50"	2,68
55"	2,86
60"	3,02
65"	3,20
70"	3,36
75"	3,54
80"	3,75
84"	4,05 min.
93"	4,17 max.

Ringenes placering:	
Bundstykke	671 mm
	925 ²⁵⁴
	1148 ²⁵⁸
Topstykke	134
	318 ^{18,4}
	493 ¹⁷⁵
	652 ^{15,9}
	811 ¹⁵
	948 ^{13,7}
	1072 ^{13,4}

anneau d'apart

8 mm skydering
2 slangering.
2 slangering.
1 slangering.
1 slangering.
1 slangering.
1/0 slangering.
1/0 slangering.
1/0 slangering.
2/0 slangering.
4 1/2 topøje

anneau kete

Jim Payne	8'
0"	0,86 r
5"	1,00
10"	1,28
15"	1,55
20"	1,75
25"	1,92
30"	2,15
35"	2,35
40"	2,51
45"	2,70
50"	2,85
60"	3,00
65"	3,15
70"	3,35
75"	3,50
80"	3,70
85"	3,90
90"	4,90
95"	5,05
96"	5,05

212E	8' 0":
0"	0,94 mm
5"	1,08
10"	1,35
15"	1,58
20"	1,76
25"	1,94
30"	2,10
35"	2,25
40"	2,40
45"	2,57
50"	2,72
55"	2,90
60"	3,07
65"	3,23
70"	3,40
75"	3,58
80"	3,77
85 1/2"	4,20 min.
96"	4,33 max.

Ringenes placering:	
Bundstykke	700 mm
	944
	1161
Topstykke	134
	324
	502
	671 ⁵⁹
	833
	976
	1110

9 mm skydering
3 slangering
2 slangering
2 slangering.
1 slangering
1 slangering.
1/0 slangering
1/0 slangering.
1/0 slangering.
2/0 slangering.
4 1/2 topøje

Papier le livre de Jacobsen "STANGBYGNING"

Taperinger m. m.

Garrison's stænger:

201	7' 0":	Ringenes placering målt fra bunden af hen-		
0"	0,80 mm	holdsvis stang og han-ferrule:		
5"	0,98	Bundstykke	636 mm	7 mm skydering
10"	1,22		840	1 slangering
15"	1,43		1018	1 slangering
20"	1,60	Topstykke	143	1/0 slangering
25"	1,77		327	1/0 slangering
30"	1,92		500	2/0 slangering
35"	2,08		668	2/0 slangering
40"	2,23		820	3/0 slangering
45"	2,39		954	3/0 slangering
50"	2,56		c. 1056	4 topøje
55"	2,72			
60"	2,89			
65"	3,06			
70"	3,32			
75"	3,68 min.			
84"	3,84 max.			

206	7' 6":	Ringenes placering:		
0"	0,80 mm	Bundstykke	661 mm	8 mm skydering
5"	0,99		881	2 slangering
10"	1,27		1084	2 slangering
15"	1,49	Topstykke	153	1 slangering
20"	1,67		347	1 slangering
25"	1,83		537	1/0 slangering
30"	1,99		722	1/0 slangering
35"	2,14		881	2/0 slangering
40"	2,30		1021	2/0 slangering
45"	2,50			4 1/2 topøje
50"	2,62			
55"	2,80			
60"	2,97			
65"	3,14			
70"	3,30			
75"	3,50			
80"	3,89			
83"	3,93 min.			
90"	4,03 max.			